# **Communication Accessories**

#### **Phone-Com Systems**



The Phone-Com intercom system provides direct, wired, point-to-point communication, operates on 12 VDC, constructed of high-impact plastic and are available in either classic white or traditional black. Wall mounting bracket is provided. Available models: PI-2 and PI-10.

**PI-2:** Designed for communication between only two points. A single call a buzzer and illuminates an indicator lamp on the companion phone. or as a set with 40' of interconnect wire, fuse, terminal lugs and mounting

**PI-2 SET**: Two station phone set, 40' interconnect wire, fuse, lugs, mounting hardware; 5 lbs.

**PI-10:** For multiple station calling capability. Up to 10 phones may be interconnected, and each phone has 10 call buttons. Sold individually-wiring requirements in the next column.

#### Accessories:

22 AWG Wire: 5, 10 or 15 conductor; sold per foot.

BUZZER: External buzzer for use in high-noise areas, 1 lb



## **AQ Series Waterproof Radio Covers**



The case is made of super-tough, UV resistant PVC, which is engineered with enough

flexibility to facilitate easy operation of knobs and keypads. Transparent design allows easy reading of digital displays.

Sound is virtually unimpeded and RF transmission is unaffected. A quick release clip allows easy insertion and removal of the radio and a handy lanyard provides extra security when hands are wet. But if the radio falls into deep water, no problem! Safely inside the AQ case, it will float!


#### Model

**AQ-10L/R** For compact hand-held radios. New reversible design accommodates both left and right hand antennas; Replaces AQ-10

AQ-20L/R For standard size hand-helds. New reversible design accommodates both left and right hand antennas; Replaces AQ-20L and AQ-20R

#### Dimensions in inches

A=Overall height of radio/phone with antenna extended
B= Height of radio/phone body
C=Combined width and depth of radio/phone body



Model	A	В	С
AQ-20L/R	15.7"	7.8"	5"
AQ-10L/R	13"	6.1"	4.1"

Weight (all models): 1 lb.

### **Indoor/Outdoor Paging Speakers**



Clear, distortion-free waterproof speakers are ideal for paging and alarm systems. Constructed of high impact plastic with stainless steel hardware. Impedance (all models) 8 Ohms.

Model	Output Nominal/Peak	Weigh
PA-8W	8 watts / 12 watts	l lb.
PA-30/20	30 watts / 20 watts	3 lbs.
PA-40/30	40 watts / 30 watts	5 lbs.
PA-60/40	60 watts / 40 watts	8 lbs.

Note: Model PA-60/40 is a commercial grade horn which also features excellent sensitivity as a microphone for use in talk-back systems.



Microphone Clips

not in use. Lift to release.

All stainless steel. For securing

standard VHF microphone when

PA-8W

### Antenna/Coax Switches

#### Manual

Model: CS-201

Two position switch allows manual selection of one of two antennas with a single radio or one of 2 radios with a single antenna. Die cast aluminum case.

Power: 1.5 kW peak, 1kW continuous

Impedance: 50 ohm Connectors: S0-239/UHF Weight: 1Lb., .5Kg.



# Remote

Model: RCS

Operates on 12 VDC, single pole, double throw. Permits remote selection of two antennas with a single radio.

Power:1Kw.
Impedance: 48 ohm
Coil Current: 250 m A
Connectors: SO-239/UHF
Weight: 1 Lb., .5 Kg.



# Powering the Network