



# LPX Series

## Next Generation Low Profile Power Supplies

LPX-10, LPX-14, LPX-18, LPX-25



*The LPX Series is the next generation of DuraComm's popular and reliable LP desktop power supply. We enhanced the electronic filtering and noise shielding, added auto ranging AC input, and adjustable DC output, all while maintaining the rugged 7 inch standard design. The improved efficiency meets DoE level VI green energy standards.*



	LPX-10	LPX-14	LPX-18	LPX-25
Input Voltage (Nominal)	90-264 VAC or 127-370 VDC			
Output voltage	13.8V			
OUTPUT RIPPLE & NOISE (ON FULL LOAD, PEAK TO PEAK)	150 mV			
OUTPUT CURRENT, CONTINUOUS	8.7A	13A	17.4A	26A
CURRENT LIMIT	10.9A	16.3A	21.7A	32.6A
COOLING	Convection Cooled			
PROTECTIONS	Overload, over voltage, and over temperature			
ENVIRONMENTAL TEMPERATURE RANGE	-30 to +70 °C		-22 to +158 ° F	
AC INPUT	Detachable power cord C/W NEMA 5-15P plug			
DC OUTPUT	Terminals w/ recessed hole DIA. 0.16" (4 mm) with set screw			
DIMENSIONS, (L x W x H) Shipping	280 x 230 x 60 mm		11.02 x 9.06 x 2.36in	
DIMENSIONS, (L x W x H) Product	192 x 178 x 45 mm		7.56 x 7.00 x 1.77 in	
WEIGHT	1 KG		2.21 LB	

**\*NOTE: Specifications are subject to change without notice**